Bell Hot Stab

Description:

In the event of a bell separation the hot stab unit is an emergency device installed on the side of the bell that allows the interfacing of a secondary / emergency umbilical cord to the bell, thus maintaining life support while a rescue is underway. The unit has 2 modules, one for electric

interfacing and the other for liquids and gases. During normal operation, the units on the bell are fitted with blanking plugs which seal off the system.

Specifications:

Hot Water Port: 1/2" NPT Gas Supply Port: 1/2" NPT & 1/4" NPT

Electric Supply: power & audio



Order Detail:

Bell Hot Stab - External ROV Plug:

D-BE-009

Hydra 500 Carbon Dioxide Scrubber


Description:

With a high reliability and simple design, the Hydra 500 gives you a neat, easily cleanable and compact scrubber. The size enables it to fit through most medical locks and equipment locks.

Specification:

Length: ± 260mm
Width: ± 250mm
Height: ± 270mm
Weight: ± 5.2kg
Operating Depth: up to 300msw
Gas Flow: 420Ltr/min (actual)

Gas Flow: 420Ltr/min (actual)
Canister Capacity: 4.5Ltr
Power Requirements: 12/24VDC
(current draw = 1Amp at depth)
Electrical Connector: MCIL3F
Locking Sleeves: DLSA-F



Order Detail:

Hydra 500 Carbon Dioxide Scrubber 24 VDC:

D-HE-34

For Spares Refer to Hyperbaric Equipment

Hydra 501 Bell Heater

Description:

The Hydra 501 bell heater is a reliable and inexpensive bell heating / cooling solution.

Specification:

Length: ± 520mm Width: ± 310mm Height: ± 280mm Weight: ± 12.7kg

Operating Depth: up to 300msw Gas Flow: 420Ltr/min (actual) Heating Capacity: 2.5kW Power Requirements: 12/24VDC (current draw = 1Amp at surface) Electrical Connector: MCIL3F Locking Sleeves: DLSA-F Connection Size: 3/4" NPT

female fitting



Order Detail:

Hydra 501 Bell Heater:

D-HE-36

For Spares Refer to Hyperbaric Equipment

