Dual-Pin Banana Plugs

Description:

A high-quality, dual pin-top Banana Plug ideal for use with a variety of communicators.



Order Detail:

Banana Plug, Dual Pin, Red	D-C-512
Banana Plug, Dual Pin, Black	D-C-513
Banana Plug, Dual Pin, Yellow	D-C-514

Slide Terminal Gel-Cell Battery

Description:

12VDC Rechargeable Slide Terminal Gel-Cell Battery

Specifications:

Standby Use:

Voltage Regulation: 13.6 -1 3.8v

Initial Current: 1.1A

Cyclic Use:

Voltage Regulation: 14.5 - 14.9v

Initial Current: 2.2A



Order Detail:

Slide Terminal Gel-Cell Battery

D-C-515

External Battery Charger

Description:

This Battery Charger can be left on charge indefinitely without damage to the battery or communicator. The charger can be used to power the communicator in locations where AC power is available without the possibility of harm to divers due to its medical grade isolation. This isolation protects divers from hazardous AC currents. It is light and provides protection against reverse battery connection, AC power surges up to 4,000 VAC and has a wide temperature range from -40° to 158°F (-40 to +70°C).

Features:

- Medical grade isolated constant current/constant voltage battery charger
- Input protection circuitry protects against voltage surges up to 4,000 VAC
- Output protection circuitry protects against reversed battery connections
- Worldwide input voltage range

Compatible with:

- 2-Diver Amcom ™ II series Standard
- 2-Diver Amcom ™ II series Deluxe
- 2-Diver Amcommand ™ II Air Control System
- 2-Diver Amcommand ™ II Air Control System with Heating Element
- 2-Diver Amcommand ™ II Air Control System with Dual HP Regulators



Amron, External Battery Charger D-C-516

