SP-100D, Surface Buddy Phone

Specifications:

Length: 230mm Width: 200mm Height: 90mm Nominal Range:

50m - 500m depending on sea conditions and noise levels Reference Frequency: 32.768kHz upper single

sideband

Audio Bandwidth: 300Hz - 3000Hz

Automatic Gain Control: Greater than 100 dB Transmitter / Audio Output:

1/2 Watt (Transmitter) ½ Watt (Speaker)

Microphone:

Hand-Held, Push-To-Talk, dynamic, 500 ohm. impedance

Transducer:

Encapsulated ceramic attached to a 35ft cable with connectors Receiver Sensitivity: Greater than 100 dBv

Squelch:

Digital, using human voice recognition

Battery Type / Life:

8 AA Alkaline batteries: 10 hours

16 AA Alkaline batteries:

20 hours (nominal) Low Battery Alarm:

1 beep every 60 sec when battery level is below 7V

Record-Out:

Line level via panel RCA jack

External Power:

12V, DC at minimum of 1 amp. access via front panel mini

double banana plug

Compatible With:

XT-100-H Buddy Phone MKII-BUD/S Buddy Phone D2 RX-100-D2-A Buddy Phone SCU-BUD/S Buddy Phone STX-101 Aquacom OR-BUD/S Buddy Phone SSB-2010 Aquacom TEC-BUD/S Buddy Phone SSB-2000/1 Aquacom STX-100 Buddy Phone



Order Detail:

Buddy Phone, 2 Channel Surface Station

D-C-508

RX-100, Buddy Phone

Specifications:

Weight in Air: 198.45g Nominal Range: 50m - 500m depending on sea conditions and noise levels Reference Frequency: 32.768kHz upper single sideband

Audio Bandwidth:

300Hz - 3000Hz Automatic Gain Control:

Greater than 80 dB Transmitter / Audio Output:

Ceramic with dynamic depth

compensation

Transducer: Ceramic cylinder

Operating Depth: 40m of sea water

Battery Type / Life: Alkaline 9V "transistor" type OTS special high energy NiMH 9.6V rechargeable (RBN-9H)

Compatible With:

XT-100-H Buddy Phone MKII-BUD Buddy Phone D2 SCU-BUD/S Buddy Phone SP-100D-2 Digital Buddy Phone TEC-BUD/S Buddy Phone SSB-2010 Aquacom SSB-1001B Aquacom STX-101 Aquacom SSB-2000/1 Aquacom STX-100 Buddy Phone



Order Detail:

Buddy Phone, Receive Only

D-C-509





