Chamber Speaker 2300

Description:

The speaker provides communication between the operator and the chamber. External chamber speaker can be ordered with or without headset Jacks. The housing is 20 gauge steel, black and includes

mounting bracket and screw terminals.

Specifications:

Width: 103mm Depth: 57mm Height: 114mm

Acoustic Output Power:

15 Watt, 8 ohm.



Order Detail:

Two Way External Chamber Speaker

D-C-491

Chamber Speaker 3111

Description:

Two-Way Speaker, Call Switch, Chamber to Dive Control (DC). Head Set jack is wired for conference style communications (duplex). Optional headset permits conversation without disturbing other chamber occupants.

Individual connections for headset and speaker allow DC to continue chamber monitoring while communicating with a person using the headset. The unit features Push-to-call function. The housing is die-cast zinc with grey epoxy powder-coat.



Order Detail:

Two Way Speaker With Call Switch And Headset Jack

D-C-492

Chamber Speaker 3115

Description:

Provides communication between operator and chamber. Speaker on/off switch for private conversations when using a headset. Headset connection is wired for conference mode operation (no Push-to-Talk). The housing is die cast zinc with grey powder coat with 300 series stainless steel front panel

Specifications:

Width: 140mm Depth: 102mm Height: 140mm

Acoustic Output Power:

15 Watts, 8 Ohm



Order Detail:

Talk Back Speaker D-C-493

Bunk Box 3130

Description:

Provides a soft and relaxing sound for the harsh acoustics of a decompression chamber. Input connection is 1/2" conduit with strain relief. The housing is aluminum with epoxy powder coat, stainless steel grill and

aluminum back mounting bracket.

Specifications:

Width: 229mm Depth: 102mm Height: 229mm

Acoustic Output Power: 12 Watts, 8 Ohm



Order Detail:

Chamber Entertainment Speaker

D-C-494