

Fluorescein Dye Detection System

oe2800/1



The Standard oe2800 consists of

- 1 off oe14-366f / oe14-367f Underwater Camera
 - 2 off oe11-135F Underwater Lamp
- Baseplate

- Leak Detection
- Cost Effective
- Rapid Deployment

The Kongsberg Maritime Fluorescein Dye detection package is based on the highly successful OE14-366 ROV zoom inspection camera and the OE11-135 underwater floodlight. Modification of the colour temperature output of the lamp allows fluorescein dye to fluoresce when illuminated. Modification of the light wavelength response of the camera allows the camera to only detect the wavelength of light corresponding to the dye fluorescence. This system allows for easy detection of leaks during integrity testing.

The system is supplied with a baseplate to ensure that convergence of the lamp beam and camera field of view occurs at around 2 metres. This innovative solution to leak detection offers significant improvements in detection speed and operational costs.

A variation of the system for diver use is also available.

**KONGSBERG**

telephone: +44 (0)1224 226500

fax: +44 (0)1224 226501

email: camera.sales.uk@kongsberg.com

web: www.kongsbergmaritime.com

oe14-366f / oe14-367f Underwater Camera

oe14-366f/7f



- 12:1 Zoom
- Fluorescein Dye Detection
- Leak Detection

The Kongsberg Maritime OE14-366 (PAL) and OE14-367 (NTSC) Colour Zoom Cameras use the latest Hyper-HAD solid state sensor to provide excellent light sensitivity and image definition.

These cameras have been designed to offer maximum performance and flexibility for ROV inspection tasks.

The OE14-366 has now been modified to create a variant for Fluorescein Dye detection, the OE14-366F. The OE14-366F enjoys all of the features of the OE14-366 but has been additionally adapted to detect the wavelength of light emitted by Fluorescein Dye when excited.

Standard Features**Electrical**

Horizontal Resolution	460 TV Lines for OE14-366F 470 TV Lines for OE14-367F
Light Sensitivity	0.1 Lux (faceplate)
Sensor Type	1/3" Hyper-HAD CCD
Signal to Noise Ratio	>48dB (weighted)
Scanning	625 Line / 50 Hz PAL for OE14-366F 525 Line / 60 Hz NTSC for OE14-367F
Power Input	Constant Voltage 16V - 24V dc 550mA maximum
Video Output	1V Pk - Pk composite video into 75Ω
Focus / Zoom Control	Standard Single-Wire Tri-state
Electro-Magnetic Compatibility	EN50081-1 Emission / EN50082-1 Immunity

Environmental

Water Depth	3,000 metres, deeper options available
Temperature	Operating -5°C to +40°C Storage -20°C to +60°C
Vibration	10g, 20 - 150Hz, 3-axes (non-operating)
Shock	30g peak, 25mS half-sine pulse

Optical

Detection	Fluorescein Dye detection system fitted
Zoom Lens	12:1 Magnification, 5.4mm to 65mm f/1.8 - 2.7
Water Compensation	Multi-Element Optical Compensator
Iris Control	Automatic
Focus Control	Remote Control, 0mm to Infinity
Angle of View	55° (min. Zoom) to 5.3° (max. Zoom) diagonal, in water

Mechanical

Size	Diameter	80mm (3.15") main body
	Diameter	93mm (3.66") rubber guard
	Length	175mm (6.89") exc. connector
Weight	Air	1.8 Kg (4.0 lb.)
	Water	1.0 Kg (2.2 lb.)
Standard Housing	6Al/4V ASTM B 348 Titanium Alloy	
Connector	Sea-Con FAWM-8P-BCRA (or equivalent) Other Connector options available	

**KONGSBERG**

telephone: +44 (0)1224 226500

fax: +44 (0)1224 226501

email: camera.sales.uk@kongsberg.com

web: www.kongsbergmaritime.com

Lamp

oe11-135f



- Adapted Colour Temperature
- Pressure Balanced
- Quick Detection

Kongsberg Maritime's range of underwater lamps have been designed to address the specific requirements of high quality underwater video inspection and observation tasks.

The OE11-135 is a compact high power lamp specifically designed for diver and ROV deployment applications.

The OE11-135 has now been modified to create a variant for Fluorescein Dye detection, the OE11-135F. The OE11-135F enjoys most of the features of the OE11-135 but has been adapted by the incorporation of a filter system which modifies the lamp colour temperature. This modified output allows Fluorescein Dye to fluoresce when illuminated.

Standard Features**Electrical**

Lighting	Plug-in high efficiency quartz halogen bulb. Fully variable output
Power	115V / 300 Watt
Reflector	Integral internal body reflector

Environmental

Depth Rating	3,000 metres standard
Temperature	Operating -5°C to +40°C Storage -20°C to +60°C
Vibration	10g, 20 - 150Hz, 3-axes (non-operating)
Shock	30g peak, 25mS half-sine pulse

Mechanical

Size	Diameter 93mm (3.66") rubber guard Diameter 80mm (3.15") main body Length 48mm (1.9") rear body Weight Air 0.7 kg (1.54 lbs) Water 0.5 kg (1.10 lbs)
Corrosion Protection	Hard Anodised, Black Dyed
Housing	6082-T6 Marine Grade Aluminium
Connector	E0 Type (or equivalent) 59F2M Right-angle Connector options available

Optical

Light Output	Colour temperature modification system fitted. Filter system oil filled and pressure balanced to match depth rating.
--------------	--

**KONGSBERG**

telephone: +44 (0)1224 226500

fax: +44 (0)1224 226501

email: camera.sales.uk@kongsberg.com

web: www.kongsbergmaritime.com