



Model 106 Current Meter

The Model 106 Current Meter is a light weight, cost effective impeller current meter, designed for real time current measurement or short to medium term autonomous deployments. Titanium construction ensures durability, and the optional temperature and pressure sensors increase the versatility of the instrument. Ideal for use in rivers and coastal applications, or from small boats, the Model 106 is simple to use with either the Windows based DataLog X2 software supplied, or an optional dedicated display unit.

DATA SHEET

Product Details



CURRENT



DATALOG X2 &
CDU EXPRESS SOFTWARE

Valeport Limited
St. Peter's Quay, Totnes,
Devon TQ9 5EW United Kingdom

Telephone: +44 (0) 1803 869292
Email: sales@valeport.co.uk
www.valeport.co.uk



Sensors

Current Speed

Type	High Impact Styrene Impeller
Size	125mm diameter by 270mm pitch
Range	0.03 - 5m/s
Accuracy	±0.004m/s (below 0.15m/s) +/-1.5% of read (above 0.15m/s)

Direction

Type	Flux gate compass
Range	0 - 360°
Accuracy	± 2.5°
Resolution	0.5°

Temperature

Type	Thermistor
Range	-5 - 35°C
Accuracy	± 0.2°C
Resolution	0.01°C

Pressure

Type	Strain Gauge Transducer
Range	50, 100, 200 or 500 dBar
Accuracy	± 0.2% Range.
Resolution	0.025% Range

Data Acquisition

The current meter works on a basic 1 second cycle, during which the impeller counts are taken and a single compass heading reading is made. From this, East and North velocity vectors are calculated, which are then summed over the averaging period. The additional parameters of temperature and pressure (if fitted) are sampled once every sample period, and averaged over the averaging period.

Data Recovery

Direct to PC via communications port. Maximum RS232 data rate of 19200 baud.

Switching On/Off

The meters are switched on and off through software control, either by the DataLog X2 software or by using the Model 8008 CDU. However, for autonomous, self-recording operation the 106 is supplied with a SubConn switch cap that fits in place of a direct cable connection.

Display unit

The Model 106 may be used with a dedicated display unit for real time operations allowing instrument setup and data display

Size	244 x 193 x 94mm, 2kg
Protection	IP67 (10 secs @ 0.3m)

Memory

512 Kbyte Solid State Memory. Each parameter record uses 2 bytes. As an example, this gives a duration of over 1 week with full parameter sampling every 10 seconds, or 220 days with sampling every 5 minutes

Power

Internal	1 x D cell. 1.5v alkaline cell gives approximately 30 days at 10 second sample rate, or 56 days at 5 minute sample rate. 3.6v Lithium cell gives approximately 90 days at 10 second sample rate, or 180 days at 5 minute sample rate
----------	--

External	For external supply, 12-20v DC is required. Power can also be taken from the Model 8008 CDU
----------	---

Communications

Fitted with SubConn MCBH10F (Brass)
RS232 to PC over cable lengths up to 200m
Digital Current Loop to Model 8008 CDU, or to PC over longer cable lengths (requires additional adapter)

Physical

Instrument	
Materials	Titanium, acetal and ABS plastic
Size	640mm x 50mm Ø tail 133mm wide x 270mm high
Weight	3kg (air), 2kg (water)
Depth Rating	500m

Shipping

Model 106 Size	84 x 42 x 39cm
Model 106 Weight	17kg
50m Cable Size	42 x 33 x 49cm
50m Cable Weight	11kg

Software

System is supplied with DataLog X2 Windows based PC software, for instrument setup, data extraction and display of tabular and graphical data plots. DataLog X2 is licence free

Ordering

0106001SC	Model 106 Self-Recording/Direct Reading Fitted with: • Speed and Direction sensors Supplied with: - Communications lead (3m Y lead) - Switch Cap - Software - Operating manual, Tool kit and transit case
0106003SC	As 0106001SC plus Temperature option
0106004SCXX	As 0106001SC plus Depth option
0106005SCXX	As 0106001SC plus Temperature & Depth
	Note: (XX denotes pressure transducer range)
0105005SC	Control Display Unit set, comprising deck lead and Model 8008 CDU

Datasheet Reference: Model 106 Current Meter | August 2022

As part of our policy of continuing development, Valeport Ltd. reserve the right to alter at any time, without notice, all prices, specifications, designs and conditions of sale of all equipment - Valeport Ltd © 2022

